

TONG CHENG IRON WORKS CO., LTD.

Business office Factory:

No. 16, Ta Chin St. Sec. 2, Taichung, Taiwan, 40242

TEL:886-4-2261-2135

FAX: 886-4-2262-8246

website : www.swanair.com.tw

E-Mail:swantc@swanair.com.tw

Reg. Office:

116, Shing Yee St., Taichung, Taiwan, 40144

TEL:886-4-2261-2135

FAX: 886-4-2261-5465



Since 1956

www.swanair.com.tw



東正鐵工廠股份有限公司
TONG CHENG IRON WORKS CO., LTD.

公司: 台中市東區信義街116號

TEL:886-4-2261-2135 FAX:886-4-2261-5465

廠址: 台中市南區大慶街二段16號

TEL:886-4-2261-2135 FAX:886-4-2262-8246

台北營業所: 新北市五股區五權五路43號

TEL:02-2299-1285 FAX:02-2298-2296

台中營業所: 台中市南區大慶街二段16號

TEL:04-2261-2135 FAX:04-2261-5465

台南營業所: 台南市永康區中正南路635號

TEL:06-253-9848 FAX:06-253-9849



DRV-215 & SK-101

Oil-less Portable Air Compressor

無油式低馬力高壓力空壓機





DRV-215 Portable Air Compressor

DRV-215低馬力高壓力空壓機

Features

- **Easy to carry on, space saving:**
Great flexibility, can be portable to anywhere any time.
- **Large capacity:**
55L large air tank with inner epoxy coating (option) to prevent from corrosion inside the air tank, and keeping clean air quality. Besides, the water drainer design on the top of air tank is easy for water draining.
- **Pressure is adjustable:**
Working pressure can be adjusted from 1 to 7 kg/cm² for various applications to save time, energy and meet with your working demands.
- **Silent operation, low noise level:**
With soundproof design to provide a low noise working environment.
- **Oil-less air, environmental friendly:**
no need of lubricant, no oil pollution, supply clean and oil-less air.

Cabinet Structure

- Powder coating, exquisite appearance and long durability.
- Adopt advanced sound-absorbing material, shock-resistant structure, low noise and low vibration.
- Cooling system, with high efficient exhausting fan to ensure long service life of the unit.

箱體結構

- 粉體塗裝，外觀精美耐用。
- 採用高級吸音材、防震結構，運轉低噪音、低震動。
- 冷卻系統，採用效能佳排風扇，確保機體、組件壽命。



DRV-215

Air Receiver

- Inner surface is with epoxy coating to prevent corrosion inside the tank (option).
- High strength steel plate, safe and reliable.
- Safety valves are installed to ensure safe operation.

儲氣桶

- 桶內環氧樹脂塗裝，無銹蝕之慮。
- 採用高強度鋼板，安全可靠。
- 裝有安全閥，確保使用安全。



特性

- 搬運靈活，省空間：
機動性佳，任您隨心拖拉走。
- 潔淨保存，大容量：
55L超大儲氣桶，桶內塗裝防止冷凝水銹蝕儲氣桶內部，保存良好的空氣品質，桶上洩水超方便。
- 壓力選擇，人性化：
工作使用壓力，1-7 kg/cm²壓力可調整，用途廣，省時省能源，契合作業上的使用需求。
- 安靜運轉，低噪音：
貼心的隔音設計，讓您在低噪音的工作環境。
- 無油空氣，超環保：
不需使用潤滑油，無油污染，乾淨無油。

Multi-functional Panel

- Adjustment of outlet pressure.
- Outlet pressure indicator.
- Vessel pressure indicator.
- Power switch.
- Motor current protector.

多功能面板

- 出口壓力調整。
- 出口壓力顯示錶。
- 桶內壓力顯示錶。
- 電源開關。
- 馬達電流保護器。

Control System Components

- With no-load starting solenoid valve to ensure the smooth re-starting of air compressor when the power is off during operation.
- High reliability components: pressure switch, check valve, safety valve, solenoid valve.

控制系統元件

- 附有無負荷啟動電磁閥裝置，運轉中斷電，可順利再啟動運轉。
- 採用高信賴度組件：壓力開關、逆止閥、安全閥、電磁閥。

Oil-less Air Compressor

- Provide pure clean air.
- Low noise and high efficiency.

無油式空壓機

- 提供氣源潔淨無油。
- 低噪音，高效能。

Drain Valve On The Top Of The Air Tank

- Easy to drain water from air tank.

桶上洩水閥

- 儲氣桶洩水簡單方便。

Air Outlet Cock Valve

- Compressed air outlet.

空氣開關

- 壓縮空氣出口。

Specs. 規格 Model 型式	Motor (kw/hp) 馬 達		Working Pressure (kg/cm ² .g) 使用壓力	Displacement (l/min) 活塞變位量		Tank Capacity (liter) 儲氣桶容量	Dimension LxWxH (mm) 尺 寸	Weight (kg) 重 量
	1.1	1.5		50HZ	60HZ			
DRV-215	1.1	1.5	7	200	241	55	765X385X842	64

*Keep on developing for excellence, we reserve the right to alter specifications without prior notice.

*Other special discharge, pressure and drive type are available upon request!

*本公司不斷研究改進，規格如有變更，恕不另行通知。

*規格外之壓力、排氣量、空壓設備，詳細資料歡迎與本公司洽詢。

SK-101 Portable Air Compressor

SK-101低馬力高壓力空壓機

Features

- Max working pressure up to 10 kg/cm².
- Clean oil-less air.
- Un-load starting and over load protection.
- Portable design for easy transportation.
- Stainless air receiver can be additionally ordered for expanding air tank capacity.
- Different working pressure settings are available for various applications.
- High cooling efficiency to reduce the operating temperature.
- Self-lubricating piston rings and wear-resistant cylinder will make the air compressor more durable.

特性

- 使用工作壓力達到 10 kg/cm²。
- 清淨無油壓縮空氣。
- 無負荷起動與過載保護。
- 輕巧移動方便，預備桶可以擴充。
- 可以設定不同使用壓力。
- 冷卻效果佳、更耐用。
- 自潤滑活塞環與耐磨汽缸更可靠信賴度佳。

Light, Silent, Clean

輕.靜.淨



SK-101



Air Compressor

- Oil-less bare pump provides pure clean oil-less compressed air.
- Air output with dual regulator valve devices to preset different working pressure according to different applications.
- Easy to move, with drain valve being located on the top of the air tank for easy operation.

空壓機

- 無油式機體，輸出潔淨無油壓縮空氣。
- 空氣氣源輸出，附有雙調壓閥裝置，可依不同用途設定不同使用壓力。
- 輕巧移動方便，桶上洩水裝置作業容易方便。

Control System Components

- High reliability components: pressure switch, check valve, pressure gauge, safety valve.
- With no-load starting-up feature to ensure smooth start-up of the air compressor.
- Motor is equipped with over-current protector.

控制系統元件

- 採用高信賴度組件：壓力開關、逆止閥、壓力錶、安全閥。
- 附有無負荷啟動裝置，確保空壓機順利啟動運轉。
- 馬達附有電流保護器裝置。

Air Receiver

- Stainless steel plate material, to ensure corrosion-resistant (optional).
- Safety valve device to comply with safety regulations, and ensure safety operation.
- Powder coating, exquisite appearance, painting is durable and not easy to peel off.

儲氣桶

- 採用不銹鋼鋼板材質，無銹蝕之慮。
- 安全閥裝置，符合安全規範設定，確保使用安全。
- 粉體塗裝，外觀精美，塗裝不易脫落。

Specs. 規格 Model 型式	Motor (kw/hp) 馬 達		Working Pressure (kg/cm ² .g) 使用壓力	Displacement (l/min) 活塞變位量		Tank Capacity (liter) 儲氣桶容量	Dimension LxWxH (mm) 尺 寸	Weight (kg) 重 量
	0.75	1		50HZ	60HZ			
SK-101	0.75	1	10	143	172	16	420X290X580	27