ENGINE TYPE AIR COMPRSOR SERIES

 SWAN high quality air compressor pump
Engine driven
Powder coated air tank

• Engine driven

Driven by diesel power, free from limitation of power source, offer superb quality of compressed air anytime and anyplace. Able to process repairments anywhere.

Detailed specifications

Model	Power (HP)	Power (kW)	Working Pressure (kg/cm²)	Capacity (m³/min)	Tank Capacity (liter)	Dimension (mm) (L*W*H)	Weight (kg)
SVU-201E(gas)	5.5	4.13	8	0.14	85	1100x440x780 (Without Battery)	58
SVU-202E(gas)	5.5	4.13	8	0.225	85	1100x440x780 (Without Battery)	62
SVU-203E(gas)	6	4.5	8	0.355	240	1620x510x1165 (With Battery)	190
SVU-203E(diesel)	6	4.5	8	0.355	240	1620x510x1165 (With Battery)	190
SVU-205E(gas)	8	6	8	0.545	240	1525x550x1170 (Without Battery)	220
SVU-205E(diesel)	10.5	7.88	8	0.545	240	1525x550x1200 (Without Battery)	230
SWU-307E(diesel)	13	9.75	8	0.872	300	1835X650X1200 (Without Battery)	300
SWU-310E(diesel)	18	13.5	8	1.151	300	1835X650X1220 (Without Battery)	345
HVU-203E(gas)	5.5	4.13	16	0.270	237	1670x510x1165 (With Battery)	240
HVU-203E(diesel)	6	4.5	16	0.270	237	1670x510x1165 (With Battery)	240
HVU-205E(gas)	8	6	16	0.406	237	1670x550x1210(With Battery)	270
HVU-205E(diesel)	10.5	7.88	16	0.406	237	1560x550x1250 (Without Battery)	275
HWU-307E(diesel)	13	9.75	16	0.606	237	1630x640x1285 (With Battery)	335
HWU-310E(diesel)	18	13.5	16	0.786	237	1630x640x1300 (With Battery)	372

1. The specification of the above air compressor is for 50Hz's, other discharge, pressure and drive type available upon request

2. SWAN Air Compressors keep on searching for excellence, we reserve the right to alter specifications without prior notice.



永 丞 缬 ≭ 砍 股份有限公司 TONG CHENG IRON WORKS CO., LTD. No. 16, Sec. 2, Ta Chin Street, South Dist., Taichung 402026, Taiwan

MAIL swantc@swanair.com.tw TEL +886-4-2261-2135 FAX +886-4-2262-8246

